

Abstract Submitted
for the DPP07 Meeting of
The American Physical Society

Sorting Category: 5.6.4 (E)

Global energy confinement studies on the Pegasus Toroidal Experiment¹ D.J. BATTAGLIA, M.J. FROST, G.D. GARSTKA, A.C. SONTAG, E.A. UNTERBERG, G.R. WINZ, University of Wisconsin-Madison — Recent studies have shown that low-recycling walls significantly enhance L-mode energy confinement [1]. Discharges on Pegasus suggest a low-recycling regime is obtained using titanium gettering and cryogenic pumping. When the external gas supply is terminated during an established discharge, tangential H_α and visible light signals drop to 5% of their initial levels within 5 ms. Wall recycling is measured using the density decay rate, and its effect on particle and energy confinement on Pegasus is explored. Initial global energy confinement times of $\tau_E = 2 - 4$ ms were calculated for $I_P \sim 0.15$ MA L-mode discharges. Scans of plasma current and line-averaged density are used to benchmark τ_E measurements against empirical L-mode scaling laws. These initial τ_E measurements indicate the H-mode power threshold as given by the ITPA04 scaling [2] can be exceeded in diverted Ohmic discharges on Pegasus.

[1] Majeski, R. *et al.* *Phys. Rev. Lett.* **97** 2006 075002

[2] Takizuka, T. *et al.* *Plasma Phys. Control. Fusion* **46** 2004 A227

¹Work supported by U.S. DOE Grant DE-FG02-96ER54375

Prefer Oral Session
 Prefer Poster Session

Gregory Garstka
garstka@engr.wisc.edu
University of Wisconsin-Madison

Date submitted: 20 Jul 2007

Electronic form version 1.4