

**Towards a Predictive Capability for Local Helicity Injection Startup**<sup>1</sup> J.L. BARR, M.W. BONGARD, M.G. BURKE, R.J. FONCK, E.T. HINSON, B.T. LEWICKI, J.M. PERRY, A.J. REDD, D.J. SCHLOSSBERG, University of Wisconsin-Madison — Local helicity injection (LHI) is a non-solenoidal tokamak startup technique under development on the Pegasus ST. New designs of the injector cathode geometry and plasma-facing shield rings support high-voltage operation up to 1.5 kV. This leads to reduced requirements in injector area for a given helicity input rate. Near-term experiments in Pegasus are testing the gain in  $I_p$  obtained with a  $1.5\times$  increase in the helicity input rate and the efficacy of helicity injection in the lower divertor region. A predictive model for LHI is needed to project scalable scenarios for larger devices. A lumped-parameter circuit model using power and helicity balance is being developed for LHI on Pegasus-U and NSTX-U. The model indicates that MA-class startup on NSTX-U will require operating in a regime where the drive from LHI dominates the inductive effects arising from dynamically evolving plasma geometry. The physics of this new regime can be tested in Pegasus-U at  $I_p \approx 0.3$  MA. The LHI systems on the proposed Pegasus-U will be expanded to provide  $3 - 4\times$  helicity injection rate and the toroidal field doubled to reach this regime. Predictive models to be validated on Pegasus-U include the 0-D power balance model, NIMROD, and TSC.

<sup>1</sup>Work supported by US DOE grants DE-FG02-96ER54375 and DE-SC0006928.

- Prefer Oral Session  
 Prefer Poster Session

M.W. Bongard  
mbongard@wisc.edu  
University of Wisconsin-Madison

Special instructions: Please place as Pegasus talk 1 of 2 in the NSTX contributed oral session.
---